

ASSESSORIES



EBW 1

Art. no. 601136
Interface converter

General:
for connection of max. 7 EASYBus-modules to the RS232-interface (9-pin Dsub) of your PC.

Specifications:	
Voltage supply:	230 V AC / 50 Hz, 12 / 24 V DC on request
Power consumption:	approx. 5 W
Max. permissible sensor modules:	7 (depending on type of the used sensor modules)
Permissible cable length:	200 m (depending on type of cable and wiring)
Baud rate:	4800 Baud
Serial connection:	RS232
Electrical isolated:	yes
Overload display:	no
Short-circuit proof:	limited (approx. 30 s)
Operating temperature:	0 ... 50 °C
Humidity:	20 ... 80 % RH, non-condensing
Storage temperature:	-20 ... +70 °C
Dimensions:	112 x 80 x 45 mm (L x B x H)
Bit-Recovery	no
Scope of supply:	interface converter, 9-pin Dsub extension cable



EBW 64

Art. no. 601139
Interface converter

General:
For connection of max. 64 EASYBus-modules to the RS232-interface of your PC.

Specifications:	
Voltage supply:	230 V AC / 50 Hz
Power consumption:	approx. 15 W
Max. permissible sensor modules:	64 (depending on type of the used sensor modules)
Permissible cable length:	1000 m (depending on type of cable and wiring)
Baud rate:	4800 Baud
Serial connection:	RS232
Electrical isolated:	yes
Overload display:	yes
Short-circuit proof:	yes (passiv)
Operating temperature:	0 ... 50 °C
Humidity:	20 ... 80 % RH, non-condensing
Storage temperature:	-20 ... +70 °C
Dimensions:	100 x 75 x 110 mm (H x W x D)
Bit-Recovery	yes
Scope of supply:	interface converter, 9-pin Dsub extension cable



EBW 3

Art. no. 601137
Interface converter

General:
for connection of one EASYBus-module (e.g. EASYLOG) to the USB-interface of your PC. (Power supply: via USB)

Specifications:	
Voltage supply:	not necessary
Power consumption:	max. 0.5 W
Max. permissible sensor modules:	1 (depending on type of the used sensor modules)
Permissible cable length:	10 m (depending on type of cable and wiring)
Baud rate:	4800 Baud
Serial connection:	USB
Electrical isolated:	yes
Overload display:	no
Short-circuit proof:	no
Operating temperature:	-25 ... +50 °C
Humidity:	20 ... 80 % RH, non-condensing
Storage temperature:	-25 ... +70 °C
Dimensions:	56 x 31 x 24 mm (L x B x H)
Bit-Recovery	no
Scope of supply:	interface converter, driver CD, manual



EBW 250

Art. no. 609308
Interface converter

General:
For connection of up to 250 sensor modules via RS232, USB or network. For use as a repeater in an existing EASYBus system.

Specifications:	
Voltage supply:	110 ... 250 V AC
Power consumption:	max. 100 W
Max. permissible sensor modules:	250 (depending on type of the used sensor modules)
Permissible cable length:	1000 m (depending on type of cable and wiring)
Baud rate:	300 ... 38400 Baud
Serial connection:	RS 232, USB, network, EASYBus input (repeater function)
Electrical isolated:	yes
Overload display:	yes
Short-circuit proof:	yes (activ)
Operating temperature:	0 ... 45 °C
Humidity:	30 ... 80 % RH
Storage temperature:	-20 ... +70 °C
Dimensions:	229 x 204 x 76 (H x W x D)
Bit-Recovery	yes
Scope of supply:	interface converter, driver CD, manual

Assessories:
USB-Adapter
Art. no. 601109
Adapter for connection of a RS232-interface converter to USB-interface