

3-pin. probe for level control (conductive)

**GNS-3P**

Art. no. 603170
3-pin. level probe

General:

- For all industrial applications
- Alarm-, Level- and Doseregulation
- Optional teflon covered staffs
- Combined with control electronics (ALSCHU 300, ALSCHU 485 OE / 3P or MINAL) an accurate liquids level control system

Specifications:

Number of electrodes:	3 pieces
Length of electrodes:	150 mm, other lengths upon request, probes can be cutted to needed length, in order to be adapted to local conditions.
Electrical connection:	2 m cable
Switching distance:	10 mm
Dimensions:	
Electrode length:	150 mm
Electrode diameter:	3 mm
Electronics box:	55 x 35 mm (W x H)
Scope of supply:	Device, manual

Option:**other length available****Teflon covered staffs**

only tip is uncovered (for electrodes used in salt water, ...)

suitable for:

Alschu 300 FG, Alschu 300 SP, ALSCHU 485 OE / 3P

3-pin. probe for level control (conductive)

**GNS-3P-SLV**

Art. no. 604786
3 electrodes with Poliolefin coating

- cooling water
- all conductive liquids

GNS-3P-SLK

Art. no. 604016
3 electrodes with Kynar coating

- food and beverage industry
- chemical industry

GNS-3P-SLE

Art. no. 603172
3 electrodes with PTFE coating


- aggressive conductive liquids

General:

- Coated electrodes
- Rugged construction, sealed
- Alarm or level regulation or dosage of liquids
- Combined with control electronics (ALSCHU 300, ALSCHU 485 OE / 3P) an accurate liquids level control system

Specifications:

Number of electrodes:	3 pieces
Length of electrodes:	500 mm, other lengths upon request, probes can be cutted to needed length, in order to be adapted to local conditions.
Electrical connection:	EN 175301-803/A plug
Process connection:	G 1", Polypropylen
Pressure max.:	6 bar
Temperature max.:	+100 °C
Protection class:	IP65
Dimensions:	SW: 40 mm A: 68 mm B: 20 mm L: 500 mm



Scope of supply: Device, manual

suitable for:

Alschu 300 FG, Alschu 300 SP, ALSCHU 485 OE / 3P