

Standard - jacket thermo elements Type K (NiCr-Ni)



MECHANICALLY ROBUST



L = 1 m, for other cable length or other accessories p.r.t. accessories

GTF101-5-xx-xxxx

Jacket thermo elements type K (NiCr-Ni) complete with cable sleeve and 1 m silicone cable (compensation line), loose wire ends

Specifications:	
Jacket material:	Inconel 600, flexible (standard)
Insulation:	highly compressed pure MgO
Thermo wires:	NiCr-Ni, DIN IEC 584, welding insulated (volt-free)
Accuracy:	optimum accuracy (cl. 1) = ± 1.5 °C or ± 0.4 % of measuring value (Almost double accuracy as compared to class 2. As a comparison with class 2: ± 2.5 °C or ± 0.75 % of meas. value)
Connecting cable:	silicone compensation line, 1 m long (max. 200 °C), loose ends. (Longer line or other material against upcharge)
Temperature application range:	-220 ... +1150 °C (Probe tip and front part; wire outlet: max. 200 °C, for cable p.r.t. accessories) (Accuracy class 1 applicable from -40 ... +1000 °C)

Recommended upper temperature limit for continuous use:			
Ø	0.5	1.0	1.5
°C	700	700	920

Accessories and spare parts:	
Clamping screw connection	Ø 1.5, 3.0 or 6.0 mm, see accessories
NST1200 „K“	Prefabricated flat connector Please specify when ordering

Special sizes and other connection cables see industry temperature probe type GTF 101 K

All thermo elements accuracy class 1 (Almost double accuracy than class 2!)

HIGHLIGHTS:

- Can be subjected to high temperatures and pressures
- Resistant to aggressive atmospheres
- Minimum dimensions, therefore short response times
- Flexible (the smaller the diameter the smaller the bending radii)
- Potential-free (thermoelement wires have no connection to the outer jacket)
- Optimum accuracy acc. to DIN IEC584 class 1

Type:	Ø mm	EL mm
GTF101-5-05-0150 Art. no. 607596	0.5	150
GTF101-5-05-0250 Art. no. 607597		250
GTF101-5-05-0500 Art. no. 607598		500
GTF101-5-05-1000 Art. no. 607599		1000
GTF101-5-05-1500 Art. no. 607600		1500
GTF101-5-10-0150 Art. no. 607601	1.0	150
GTF101-5-10-0250 Art. no. 607602		250
GTF101-5-10-0500 Art. no. 607603		500
GTF101-5-10-1000 Art. no. 607604		1000
GTF101-5-10-1500 Art. no. 607605		1500
GTF101-5-15-0150 Art. no. 607606	1.5	150
GTF101-5-15-0250 Art. no. 607607		250
GTF101-5-15-0500 Art. no. 607608		500
GTF101-5-15-1000 Art. no. 607609		1000
GTF101-5-15-1500 Art. no. 607610		1500
GTF101-5-30-0150 Art. no. 607611	3.0	150
GTF101-5-30-0250 Art. no. 607612		250
GTF101-5-30-0500 Art. no. 607613		500
GTF101-5-30-1000 Art. no. 607614		1000
GTF101-5-30-1500 Art. no. 607615		1500
GTF101-5-60-0150 Art. no. 607616	6.0	150
GTF101-5-60-0250 Art. no. 607617		250
GTF101-5-60-0500 Art. no. 607618		500
GTF101-5-60-1000 Art. no. 607619		1000
GTF101-5-60-1500 Art. no. 607620		1500

Note: Handheld instrument probes can be found in chapter handheld instruments and the appropriate devices

Handheld instrument

Display / Controller

Logger- / Bus systems

Transmitter

Temperature probe

Simulators

Alarm / Protection, Level